

### PUTSCH "EBP-950 PMCR" EDGE BANDER (W/PRE-MILL & CORNER ROUNDING)



Item # EO-230170 - Lot # 003

Current Bid:	<b>\$0</b>	<b>No Reserve</b>
End Time:	<b>275 Days, 15 Hours, 38 Minutes</b> (12/31/2025 2:30PM EST)	
Brand/Model:	<b>PUTSCH "EBP-950 PMCR"</b>	
Year MFG:	<b>2023</b>	
Machine Type:	<b>EDGE BANDER (W/PRE-MILL &amp; CORNER ROUNDING)</b>	
Serial #:	<b>23.846.002</b>	
Elect./Voltage:	<b>230 V, 60 Cy, 3 Ph.</b>	
Location:	<b>FLETCHER, NC</b>	
Dimensions:	<b>143" L x 62" W x 79" H</b>	
Weight:	<b>1160 Lbs.</b>	
Comment:	New, "Never Used" with pre-mill & corner rounding!	

#### Description:

CASADEI (PUTSCH-Branded) EBP-950 PMCR Automatic Edgebander, New, Never Used, with Pre-Mill & Corner Rounding

#### Specifications:

- Edgebanding thickness: 0.4 - 3 mm (0.02" - 0.12") Coil, 0.4 - 5 mm (0.02" - 0.20") Strip with Manual feed.
- Panel thickness 8 - 45 mm (0.31" - 1.77"), Min. panel width 95 mm (3.74"), & Min. panel length 110 mm (4.33").
- Feed speed 9 MPM (29 FPM).

#### Equipped with:

- Pre-Mill Unit, with (2) 0.75 kW (1 HP) - 12,000 RPM - 200 Hz Motors, Counter-rotation, (2) 60 mm Dia. x 52 mm H (2.36" Dia. x 2.05" H) Diamond cutterheads, Max. milling adjustment 2 mm (0.08"), & Dedicated extraction system with Blower.
- Anti-Adherence Spray Unit.
- Infrared lamp.
- PURE (PUR & EVA) Hot melt gluing system, with Teflon-coated glue pot with (6) 1,315 W Heating elements with (4) in Glue pot, (1) in Turret & (1) in Glue spreading roller, Thermostatic glue control, Automatic standby & Temperature display, and Automatic glue drainage.
- Pneumatically-operated guillotine.
- Pressure section, with (1) Large driven & (2) Small idler rollers.



## Detail Specification Sheet

---

- Feed chain, with Scratch resistant, non-slip rubber pads.
- Top pressure beam, with (2) Rows of rubber rollers.
- Safety enclosure.
- PLC Control, with ETOUCH 7" Backlit LCD touchscreen display, 99-Program Storage, & Diagnostics.

### Workstations:

- Front & Rear End Trim Unit, with 0.22 kW (1/3 HP) - 12,000 RPM - 200 Hz Motor, & (2) 80 mm (3.15") Knives.
- Top & Bottom Flush/Bevel/Radius Trim Unit, with 0.22 kW (1/3 HP) - 12,000 RPM - 200 Hz Motors, 75 mm (2.95") Dia. Cutters with Disposable knives, 2 - 3 mm (0.08" - 0.012") Radii, & 15° Bevel.
- Corner Rounding Unit, with 0.22 kW (1/3 HP) - 12,000 RPM - 200 Hz Motor, 50 mm (1.97") Diamond cutterheads, 50 mm (1.97") Vertical/Horizontal copiers for profiling straight, curved, & beveled edges, & PLC-selectable front, rear, or complete panel processing.
- Edge Scraping Unit, with 2 mm (0.08") Cutters,
- Top & Bottom Glue Scraping Unit, with 120 mm (4.72") Vertical disc copier.
- Top & Bottom Buffing Unit, with (2) 0.13 kW (0.17 HP) - 1,400 RPM Motors.
- Polishing Spray Unit, PLC-Controlled, with (2) Sprayers.

NOTE: Sold "As Is" Without Warranty!

**Final Remove Date: 12/31/2025**

Contact: **Kevin Welker - (877) 580-5844 ext. 316 - [kevin.welker@exfactoryauctions.com](mailto:kevin.welker@exfactoryauctions.com)**