

ITW DYNATEC "N05-P12-12" HOT MELT ADHESIVE EQUIPMENT**Item # GE-230224 - Lot # 025**

Current Bid: **\$0** **No Reserve**
End Time: **8 Days, 3 Hours, 15 Minutes**
(4/24/2025 2:25PM EST)
Brand/Model: **ITW DYNATEC "N05-P12-12"**
Year MFG: **N/A**
Machine Type: **HOT MELT ADHESIVE EQUIPMENT**
Serial #: **175170102620**
Elect./Voltage: **120 V, 50/60 Cy, 1 Ph.**
Location: **SPARTA, TN**
Dimensions: **0" L x 0" W x 0" H**
Weight: **75 Lbs.**
Comment: **(2) Stations!**

Description:



Detail Specification Sheet

ITW DYNATEC N05-P12-12 5 kg (11.02 Lb.) Capacity 2-Station Hot Melt Adhesive Application System, with (2) Hoses & (2) Guns

Specifications:

- Holding cap. 5 kg (11.02 Lbs.).
- Delivery rate 0.91 kg/Min. (2.01 Lbs./Min.).
- Melt rate 8 kg/Hr. (17.64 Lbs./Hr.) (Varies by adhesive type & application parameters).
- Operating temperature 40° C - 218° C (104° F - 424° F).
- Heat-up time (full): Approx. 1/2 Hr.
- Max. piston pump speed 60 Cycles/Min., Max. gear pump speed 87 RPM at 60 Hz.
- Adhesive type: Standard grade (Non-water based only).

Equipped with:

- 12:1 Piston pump.
- 3.2 cc/rev Gear pump.
- TFE Teflon-impregnated hopper, with 2,400 W cast-in tubular heaters.
- "DYNAMINI 05" Adhesive Supply Unit, with LED Display & Touchpad controls.
- 100 Ohm Platinum RTD Standard temperature sensors.
- Each station with OMRON "H5BR" LCD Timer, Gun, Hose, & Foot pedal.

Complete with:

- Operations & Service Manual.

Final Remove Date: 5/9/2025

Contact: **Kevin Welker - (877) 580-5844 ext. 316 - kevin.welker@exfactoryauctions.com**